

SUPER JUMBO TEX®

WEATHER-RESISTIVE BARRIER

60
MINUTE

PREMIER

Part of a Complete Moisture Control System

Super Jumbo Tex 60 Minute is the industry's leading 60 Minute building paper, with an unmatched track record of performance in the field. It is a member of the Jumbo Tex product line that has been chosen by builders and architects to protect over *five million* homes and commercial buildings from the problems caused by water intrusion and excessive moisture.

Super Jumbo Tex 60 Minute is used in both production and custom residential construction where there is a need for a high

performance weather-resistant barrier. The product delivers over *six times* the water protection of standard Grade "D" paper, while providing optimal breathability, to prevent the potential for moisture condensation within exterior walls. As important, it has the rugged durability necessary to resist tearing and puncturing on the jobsite. The product is part of a complete

Moisture Control System for walls engineered by the Fortifiber Building Systems Group®, which helps manage and eliminate moisture-related problems – including water-related structural failures, mold and mildew.


Unique Weather-Resistive Properties

The product is an asphalt-saturated building paper, which delivers highly reliable performance in the real world. Because it is manufactured from a base stock of kraft linerboard, Jumbo Tex is far less brittle than felt – so it is less likely to tear during installation around corners and in tight conditions. Unlike some housewraps, it will retain its weather-resistive properties when exposed to either job site surfactants or wood extracts and tannin derivatives from wood siding.

The product's 40 inch roll size makes it easier to install and store on the jobsite than other weather-resistive building materials. It is also more cost-effective than most housewraps, while offering the most formidable defense against water intrusion and moisture problems. In fact, it is possible to pay in excess of three times more for other weather-resistive barriers that cannot surpass its reliable performance behind stucco, fiber cement siding, brick, vinyl and wood siding.

Decades of Proven Performance

Super Jumbo Tex 60 Minute is a product manufactured by the Fortifiber Building Systems Group. With more than a sixty-five year history of proven performance, technical expertise and practical know-how, the company has become a trusted partner to builders, architects and code officials.



Super Jumbo Tex 60 Minute protects against water intrusion from the outside, while allowing moisture to escape from the inside.

“*The industry's leading 60 Minute building paper; with an unmatched track record of performance in the field...*”

- SOLID PROTECTION AGAINST MOISTURE PROBLEMS
- STRONG WATER RESISTANCE
- EXCELLENT PRICE-PERFORMANCE
- IDEAL BALANCE BETWEEN WATER RESISTANCE AND PERMEABILITY
- FOR STUCCO, FIBER CEMENT SIDING, BRICK, VINYL AND WOOD SIDING
- REDUCES AIR INFILTRATION



Product Description: Super Jumbo Tex 60 Minute is a premier grade weather-resistive barrier designed for use within a variety of exterior wall assemblies. It provides excellent protection from internal wall damage due to water intrusion and condensation.

Composition: Super Jumbo Tex 60 Minute is an asphalt-saturated kraft Grade "D" breather type sheathing paper.

Size & Weight: Super Jumbo Tex 60 Minute is supplied in 40" x 240 sq. ft. and 40" x 324 sq. ft. rolls. Product weight is approximately 6 lbs/100 sq. ft.

Applicable Standards: Exceeds Federal Specification UU-B-790a, Type 1, Grade "D", Style 2.

Complies with the Uniform Building Code Standard 14-1.

Complies as an alternative to the water-resistive barrier specified in Section 1404.2 of the 2006 International Building Code®.

Complies as an alternative to the weather-resistant sheathing papers specified in Section R703.2 of the 2006 International Residential Code®.

ICC ESR-1027, BOCA Evaluation Report No. 21-46, SBCCI Evaluation Report No. 2103 and CCMC Evaluation Listing No. 13142-L.

American Society for Testing & Materials (ASTM):

- ASTM D-779 - Standard Test Method for Water Resistance of Paper, Paperboard and Other Sheet Materials by the Dry Indicator Test Method
- ASTM D-828 - Tensile Properties of Paper and Paperboard Using Constant-Rate-of-Elongation Apparatus
- ASTM E-96 - Water Vapor Transmission of Materials

Physical Properties: Super Jumbo Tex 60 Minute is continually tested in accordance with ASTM procedures. The values shown in Table 1 are typical values obtained in these tests.

Limitations: Product should be covered as soon as possible. Inspect product to insure it is free of any protrusions or damage which may detract from the weather-resistive barrier integrity. Holes, tears or punctures should be sealed with

Moistop® Sealant or Fortifiber Sheathing Tape. This product is not recommended for horizontal, below grade or roofing applications.

Installation: Super Jumbo Tex 60 Minute should be installed in accordance with the local applicable building code. The International Residential Code Section R703.2 and Uniform Building Code Standard 14-1, section 1402.1, state that weather-resistive barriers should be applied horizontally, with the upper layers overlapping the lower layer by a minimum of 2" (3" is recommended), and all vertical joints should be lapped a minimum of 6". To ensure the integrity of the weather-resistive barrier system, Fortifiber strongly recommends the use of a Two-Ply Jumbo Tex product or two layers of a single ply Jumbo Tex product when used with a three-coat stucco system.

Availability: The Fortifiber Building Systems Group's products are distributed nationwide. For product information and pricing, please call a Fortifiber distributor near you. If you need assistance locating a participating distributor, please call our Customer Service Department at 1-800-773-4777.

FortiShield Warranty: Super Jumbo Tex 60 Minute is expressly warranted for a period of ten (10) years from purchase that it will perform to Fortifiber's published specifications when installed according to Fortifiber's installation procedures and accepted industry standards in a standard weather-resistive barrier application. Installation must use one or more of the following Fortifiber brand flashing products (Moistop E-Z Seal®, FortiFlash®, Moistop neXT®, or Moistop PF®) with Moistop Sealant in a properly designed and constructed wall system. In the event of a warranty claim, Fortifiber will pay the cost of materials and labor to correct problems found to be caused solely by the failure of Fortifiber's product as expressly warranted above.

THIS EXPRESS WARRANTY IS GIVEN IN LIEU OF AND EXCLUDES ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Fortifiber's sole obligations under this warranty are as set forth herein. In no event shall Fortifiber be liable for any lost revenue or profits, direct, indirect, special, incidental or consequential damages of any kind. If the installation or use of this product does not qualify for the FortiShield warranty, Fortifiber's standard warranty will apply. See fortifiber.com/warranty.htm for details.

SPECIFICATION SUMMARY: Provides secondary weather protection behind exterior cladding to prevent moisture penetration and condensation in exterior wall assemblies.

WEATHER-RESISTIVE BARRIER: Fortifiber/Super Jumbo Tex 60 Minute asphalt saturated kraft 60 minute Grade "D" breather type sheathing paper, single ply.

REFERENCE SPECIFICATION: Federal Specification UU-B-790a, Type 1, Grade "D", Style 2.

Table 1- Physical Properties

| CHARACTERISTIC | TEST METHOD | RESULTS | INDUSTRY STANDARD |
|--------------------------|---------------|---|--|
| Water Vapor Transmission | ASTM E-96 (A) | 75 grams 11 perms (MVT) | 35 grams (min.) 5 perms (MVT) |
| Water Resistance | ASTM D-779 | >60 minutes | 10 minutes |
| Tensile Strength | ASTM D-828 | MD - 70 lb. ^f /inch CD -60 lb. ^f /inch | MD - 20 lb. ^f /inch CD - 20 lb. ^f /inch |



Fortifiber Building Systems Group®
Protecting Your World from the Elements®

Call 1-800-773-4777 or 1-775-333-6400 for sales and technical assistance. On the Internet visit www.fortifiber.com.

© 2008 Fortifiber Building Systems Group. Fortifiber®, FortiFlash®, FortiShield®, Jumbo Tex®, Moistop E-Z Seal®, Moistop neXT®, Moistop PF®, Moistop® Sealant and Protecting Your World from the Elements® are trademarks of Fortifiber Corporation. 02/08